

Overview:

The FS series solar LED street light provides an integrated system for outdoor street lighting. This high-output, independently-powered fixture has a durable aluminum housing and solar panels integrated with high lumen LEDs with a high efficacy rating, which helps maximize energy efficiency. This autonomous fixture relies on solar power, with it only needing 6 hours of sun exposure to fully charge the battery and power itself for 5+ days(depending on the adjusted settinas).

Highlights:

- Unique patented smart working modes for smart and longer lighting times.
- Modular installation options(wall mount, straight/curved pole mount
- Professional optical lens, wide lighting area and more brightness
- High solar to electrical power conversion

LED Chip Info	Characteristics		
Watt Usage: 8-15W Color Temp: 5,000k	Certifications: CE, RoHS compliant		
CRI: >70 Lumens: 850-1,600LM Efficacy: 105LM/W(±10%)	2 year limited warranty. Warranty: For terms visit <u>www.poli-</u> ledsigns.com/warranty		
Lifetime: 50,000+ hours	Construction		
Application:	Operating Temp. Range	-15C°-50C°	
Areas that during the day receive a lot of sun exposure. Widely used	Housing	Aluminum	
at gardens, courtyards, driveways,	Mounting	Wall and pole	

IP rating

IP65

at gardens, courtyards, driveways, squares, parking lots, streets etc.

Performance				
Product Model:	SL-FS15	SL-FS8		
Power:	15W 8W			
Lumen:	1600LM	850LM		
Solar Panel:	Mono-crystalline Mono-crystalline silicon(9.5Wp) silicon(7Wp)			
Battery:	5400mAH/7.4V Lithium 6000mAH/3.7V Lithiur battery (total capacity 108oomAh/3.7V)			
Charging Time:	6Hrs/day	6Hrs/day		
Working Time:	Auto adjustable(5 days+)	Auto adjustable(5 days+)		
Dimensions:	492.5 x 231.9 x 58mm	428.5 x 193.7 x 52.7mm		

Ordering

Example Model Number: SL-FS15-5k-A

Series	Watt	Color Temp.	Mounting Type
SL-FS	8 8 watt 15 15 watt	50K 5000K	A Slip Fitter B Adjustable Square Pole/Wall C Square Pole/Wall

Project: QTY: Email: Phone:





CE Mark Certification European Union's mandatory conformity marking for regulating the goods sold within the European Economic Area.



2 year warranty we believe in our product quality and offer the warranty to prove it. Unlimited lifetime support is also included, call us anytime.



RoHS


IP65 Rated Maximum protection against dust and water. Withstands all weather types with silicone sealed gaskets and tight manufacturing tolerances.







Functionality



ON/OFF

This lamp is with auto-adjusting working mode, you only need to press the button once, it will work permanently.

First 5 Hrs lighting mode:




Automatically turns on to full brightness when motion is detected in the range \leq 8mtrs and then turns to weak brightness in 20 seconds of no motion.

After 5 Hrs lighting or battery capacity below 30%:



Automatically turns on to full brightness when motion is detected in the range \leq 8mtrs, then turns to weak brightness in 20 seconds of no motion, and then turns off after 5 minutes.





Mounts

Installation A: Wall Mounted

