

LUMI G Series Solar LED Bollard

PRO

Next-generation lighting for outdoor spaces.

Project:

QTY:

Email:

Phone:

Overview:


The G series street light provides an integrated system for outdoor spaces. This high-output, independently-powered fixture has a durable aluminum housing and solar panels integrated with high lumen LEDs with a high efficacy rating, which helps maximize energy efficiency. This autonomous fixture relies on solar power, only needing 8 hours of sun exposure to fully charge the battery and power itself for 5+ days (depending on the adjusted settings). There's one button on each side of the lamp, press the button to select the working mode for each side individually. The lamp can receive solar charge in any mode. Press the button one time, it's in Sensor Mode. Press the button a second time, it's in constant lighting mode. Press the button a third time, it's off. In Sensor mode the light automatically turns on to full brightness (2000lm) when motion is detected in the range ≤ 8 mtrs and then turns to limited brightness (300lm) in 20 seconds of no motion. Constant lighting mode Automatically turns on at dusk and maintains 50% brightness (1000lm) till it's dawn or power's off.

LED Chip Info	Characteristics
Watt Usage: 20W	Certifications: CE, RoHS compliant
Color Temp: 5,000k	1 year limited warranty.
CRI: >70	Warranty: For terms visit www.poliledsigns.com/warranty
Lumens: 2000LM	Construction
Efficacy: 100LM/W($\pm 10\%$)	Operating Temp. Range -20C°-60C°
Lifetime: 50,000+ hours	Housing Aluminum
Input Voltage: 100-277VAC	Mounting Concrete and soft lawn
	IP rating IP65

Application:

Areas that during the day receive a lot of sun exposure. Widely used for public places, driveway, pathway, courtyard, garden, rural roads, lawn etc.

Performance	
Product Model:	SL-G20
Power:	20W
Lumen:	2000LM
Solar Panel:	Mono-crystalline silicone (11Wp+9Wp)
Battery:	26650/6000mA/6.4V
Charging Time:	8Hrs/day
Working Time:	Sensor Mode: 4 nights+ Constant Light Mode: 2 nights+
Dimensions:	800 x 220 x 90mm



Ordering

Example Model Number: SL-G-5k

SL-G

Series	Color Temp.
SL-G	50K 5000K



- CE Mark Certification** European Union's mandatory conformity marking for regulating the goods sold within the European Economic Area.
- One year warranty** we believe in our product quality and offer the warranty to prove it. Unlimited lifetime support is also included, call us anytime.
- IP65 Rated** Maximum protection against dust and water. Withstands all weather types with silicone sealed gaskets and tight manufacturing tolerances.
- RoHS Compliant** RoHS certifies a product to be free from hazardous materials such as lead, mercury, and others to ensure a safer environment.

